



dimensions (w x d x h)	number of shelves	possibility of partition	installed power input	climatic category	LA noisiness	exhibition area	loading capacity of exhibition area	loading capacity of shelf	weight	coolant	type of glass
950 x 950 x 725	1	no	600 W	3	< 60 dB	0,65 m ²	30 kg	5 kg	117 kg	R 404A	sloping 6mm thick hardened
1250 x 950 x 725		yes	600 W			0,8 m ²			135 kg		
1400 x 950 x 725		yes	600 W			0,95 m ²			145 kg		
1700 x 950 x 725		yes	800 W			1,1 m ²			170 kg		
1900 x 950 x 725		yes	800 W			1,3 m ²			190 kg		

A self-service table refrigerating display case for the sale of goods at temperatures from +4° to +8°C . The front vertical glass with the thickness of 6 mm is tilting, set in AL elox profiles and equipped in profile. The bottom display board of stainless steel design and display case body is formed by decorated laminated wood-chip boards. Sliding door to close the refrigerated space upon request only. Static cooling. Condensate is discharged into a waste condensate vessel. Lighting by means of AL line lamps fitted with up-to-date LED chips. A digital electronic regulator for optimum control of the display case operating cycles.

The guarantee period of the product is 12 months. Guarantee and post-guarantee repairs are carried out by the producer or, after an agreement, by the service centre in the place of the user. Producer reserves the privilege for changeover.