



dimensions (w x d x h)	number of shelves	possibility of partition	installed power input	climatic category	LA noisiness	exhibition area	loading capacity of exhibition area	loading capacity of shelf	weight	coolant	type of glass
770 x 790 x 1370	3	no	850 W	3	< 60 dB	1,2 m <sup>2</sup>	30 kg	5 kg	150 kg	R 404A	perpendicular hardened side uncurved double-glazed with insulating
1070 x 790 x 1370		yes	950 W			1,7 m <sup>2</sup>			210 kg		
1370 x 790 x 1370		yes	1050 W			2,2 m <sup>2</sup>			270 kg		

A self-service refrigerating display case with double insulating glass for the sale of goods at temperatures from +2° to +8°C. The bottom display board of stainless steel design and display case body is formed by decorated laminated wood-chip boards. The shelves are made of hardened glass. The side windows are non-hardened. A sliding door double-glazed with insulating glass from the shop attendant side fitted with end stop buffers. Dynamic cooling. A cooling unit with the function of condenser self-cleaning and automatic evaporating of waste condensate by residual heat from the cooling circuit. Lighting by means of AL line lamps fitted with up-to-date LED chips. A digital electronic regulator for optimum control of the display case operating cycles.

The guarantee period of the product is 24 months. Guarantee and post-guarantee repairs are carried out by the producer or, after an agreement, by the service centre in the place of the user. Producer reserves the privilege for changeover.